



PART NO.	REMARKS	CONDUCTOR MATERIAL	CURRENT	VOLTAGE	AIR SIDE PLUG
FA10658	POWER	ALUMEL	4.8 AMPS	700V DC	NO
KT10658	POWER	ALUMEL	4.8 AMPS	700V DC	YES
FA10658-02	T/C	CHROMEL/ALUMEL	N/A	N/A	NO
KT10658-02	T/C	CHROMEL/ALUMEL	N/A	N/A	YES

RATINGS	
CONDUCTOR MATERIAL:	SEE TABLE AT LEFT
CURRENT:	SEE TABLE AT LEFT
VOLTAGE:	SEE TABLE AT LEFT
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C
TEMPERATURE WITH PLUG:	-55°C TO 125°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 			TITLE: FOUR PIN CONNECTOR		
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	1/6/2006	PART NO. (SEE TABLE) REV. A	
A1	MH	05/26/2006	MPDP0003-ST		ENG APPR.	MH	05/26/2006		SALES DWG NO. FA10658SL REV. A1