



PART NO.	CONDUCTOR MATERIAL	T/C TYPE	POWER LEAD MATERIAL	CURRENT
FA12424	CHROMEL / ALUMEL	K	COPPER	27 AMPS
FA12424-02	IRON / CONSTANTAN	J	COPPER	27 AMPS
FA12424-03	TUNGSTEN / RHENIUM*	C	COPPER	27 AMPS
FA12424-04	CHROMEL / CONSTANTAN	E	COPPER	27 AMPS
FA12424-05	CHROMEL / ALUMEL	K	NICKEL	8.2 AMPS
FA12424-06	IRON / CONSTANTAN	J	NICKEL	8.2 AMPS
FA12424-07	TUNGSTEN / RHENIUM*	C	NICKEL	8.2 AMPS
FA12424-08	CHROMEL / CONSTANTAN	E	NICKEL	8.2 AMPS

RATINGS	
VOLTAGE	3KV DC
CONDUCTOR MATERIAL:	SEE TABLE AT LEFT
T/C TYPE:	SEE TABLE AT LEFT
POWER LEAD MATERIAL:	SEE TABLE AT LEFT
CURRENT:	SEE TABLE AT LEFT
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C
TEMPERATURE WITH PLUG:	-29°C TO 218°C

*TYPE C USES COMPENSATING WIRE. MAXIMUM JUNCTION TEMPERATURE 250°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 			TITLE: ONE PAIR T/C SPADE TYPE & 3KV POWER FEEDTHROUGH		
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	1/13/2006	PART NO. (SEE TABLE) REV. B	
B1	MH	05/23/2006	MPC10050-0ST		ENG APPR.	MH	05/23/2006		SALES DWG NO. FA12424SL REV. B1