



PART NO.	REMARKS	CONDUCTOR MATERIAL	CURRENT	VOLTAGE	AIR SIDE PLUG
FA13010	POWER	ALUMEL	4.8 AMPS	700V DC	NO
KT13010	POWER	ALUMEL	4.8 AMPS	700V DC	YES
FA13010-02	T/C	CHROMEL/ALUMEL	N/A	N/A	NO
KT13010-02	T/C	CHROMEL/ALUMEL	N/A	N/A	YES

RATINGS	
VOLTAGE:	700V DC
CURRENT:	4.8 AMPS
TEMPERATURE WITHOUT PLUG:	-25°C TO 205°C
TEMPERATURE WITH PLUG:	-25°C TO 125°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

FOUR PIN CONNECTOR



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	EB	5/24/2006
A1	MH	08/23/2006	MPDP0009-1ST		ENG APPR.	MH	08/23/2006

PART NO. (SEE TABLE) REV. A

SALES DWG NO. FA13010SL REV. A1