


| PART NO. | CONDUCTOR MATERIAL | CURRENT |
|------------|--------------------|----------|
| FA11637 | COPPER | 16 AMPS |
| FA11637-02 | MOLYBDENUM | 8.5 AMPS |
| FA11637-03 | NICKEL 200 | 5 AMPS |
| FA11637-04 | 304 STN STL | 1.1 AMPS |

| RATINGS | |
|--------------|-------------------|
| VOLTAGE: | 2KV DC |
| CURRENT: | SEE TABLE AT LEFT |
| TEMPERATURE: | -25°C TO 205°C |

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

TWO 2KV FEEDTHROUGHS



SOLID SEALING TECHNOLOGY, INC.

| REV. | APP'D | DATE | SCALE 3:2 | DIMENSIONS IN INCHES [mm] | DRAWN | JM | 12/27/2005 |
|------|-------|------------|--------------|---------------------------|-----------|----|------------|
| A1 | MH | 03/21/2006 | MPDC0004-0ST | | ENG APPR. | MH | 03/21/2006 |

PART NO. (SEE TABLE) REV. A

SALES DWG NO. FA11637SL REV. A1