

PART NO.	CONDUCTOR MATERIAL
FA11632	ALUMEL
FA11632-02	CONSTANTAN
FA11632-03	TUNGSTEN 26% RHENIUM*


*USES COMPENSATING WIRE
 MAXIMUM JUNCTION TEMPERATURE 250°C

RATINGS	
CONDUCTOR MATERIAL:	SEE TABLE AT LEFT
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C
TEMPERATURE WITH PLUG:	-29°C TO 218°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE: SINGLE LEG T/C (-) SPADE TYPE FEEDTHROUGH



REV.	APP'D	DATE	SCALE 1.25:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	1/12/2006
A1	MH	05/26/2006	FTCL0024-ST		ENG APPR.	MH	05/26/2006

PART NO. (SEE TABLE) REV. A

SALES DWG NO. FA11632SL REV. A1