



PART NO.	CONDUCTOR MATERIAL	CURRENT
FA11640	COPPER	16 AMPS
FA11640-02	MOLYBDENUM	8.5 AMPS
FA11640-03	NICKEL	5 AMPS
FA11640-04	304 STN STL	1.1 AMPS

RATINGS	
VOLTAGE:	2KV DC
CURRENT:	SEE TABLE AT LEFT
TEMPERATURE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 			TITLE: <b>FOUR 2KV FEEDTHROUGHS</b>		
REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	1/12/2006	<b>PART NO. FA11640 REV. A</b>	
A1	MH	03/21/2006	MPDC0007-01		ENG APPR.	MH	03/21/2006		SALES DWG NO. FA11640SL REV. A1