

PART NO.	CONDUCTOR MATERIAL
FA13178	ALUMEL
FA13178-02	CONSTANTAN
FA13178-03	TUNGSTEN 26% / RHENIUM*


RATINGS	
CONDUCTOR MATERIAL:	SEE TABLE AT LEFT
TEMPERATURE	-269°C TO 450°C

*USES COMPENSATING WIRE
 MAXIMUM JUNCTION TEMPERATURE 250°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

SINGLE T/C (-) FEEDTHROUGH



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	5/3/2006
A1	MH	08/14/2006	FTCL0048-ST		ENG APPR.	MH	08/14/2006

PART NO. (SEE TABLE) REV. A

SALES DWG NO. FA13178SL REV. A1