

| PART NO.   | CONDUCTOR MATERIAL     |  |
|------------|------------------------|--|
| FA13192    | CHROMEL                |  |
| FA13192-02 | IRON                   |  |
| FA13192-03 | TUNGSTEN 5% - RHENIUM* |  |

| RATINGS             |                   |  |  |
|---------------------|-------------------|--|--|
| CONDUCTOR MATERIAL: | SEE TABLE AT LEFT |  |  |
| TEMPERATURE         | -269°C TO 450°C   |  |  |


<sup>\*</sup> USES COMPENSATING WIRE MAXIMUM JUNCTION TEMPERATURE 250°C

## PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

| REV. | APP'D | DATE       | SCALE 1:1   | DIMENSIONS IN |
|------|-------|------------|-------------|---------------|
| A1   | МН    | 08/14/2006 | FTCL0049-ST | INCHES [mm]   |

## THIRD ANGLE PROJECTION



|   |           |    | _          |
|---|-----------|----|------------|
| 1 | DRAWN     | JM | 5/3/2006   |
|   | ENG APPR. | MH | 08/14/2006 |

SINGLE T/C (+) FEEDTHROUGH

PART NO. (SEE TABLE) REV. A



SALES DWG NO. FA13192SL REV. A1