

PART NO.	CONDUCTOR MATERIAL	T/C TYPE				
FA11694	FA11694 CHROMEL / ALUMEL					
FA11694-02	FA11694-02 IRON / CONSTANTAN					
FA11694-03	TUNGSTEN / RHENIUM*	С				
FA11694-04	CHROMEL / CONSTANTAN	E				

RATINGS						
CONDUCTOR MATERIAL:	SEE TABLE AT LEFT					
T/C TYPE:	SEE TABLE AT LEFT					
TEMPERATURE:	-25°C TO 205°C					

*TYPE C USES COMPENSATION WIRE MAXIMUM JUNCTION TEMPERATURE 250°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION			TITLE: ONE PAIR T/C SPADE TYPE FEEDTHROUGH		
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN	DRAWN	JM	1/13/2006	PART NO. (SEE TABLE) REV. A	SOLID SEALING TECHNOLOGY, INC.
A1	MH	05/26/2006	MPCL0025-ST	INCHES [mm]	ENG APPR.	ΜΗ	05/26/2006	TARTINO: (SEE TADLE) REV.A	SALES DWG NO. FA11694SL REV. A1