



PART NO.	REMARKS	CONDUCTOR MATERIAL	CURRENT	VOLTAGE	AIR SIDE PLUG
FA10656	POWER	ALUMEL	4.8 AMPS	700V DC	NO
KT10656	POWER	ALUMEL	4.8 AMPS	700V DC	YES
FA10656-02	T/C	CHROMEL/ALUMEL	N/A	N/A	NO
KT10656-02	T/C	CHROMEL/ALUMEL	N/A	N/A	YES

RATINGS	
CONDUCTOR MATERIAL:	SEE TABLE AT LEFT
CURRENT:	SEE TABLE AT LEFT
VOLTAGE:	SEE TABLE AT LEFT
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C
TEMPERATURE WITH PLUG:	-55°C TO 125°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 			TITLE: TEN PIN CONNECTOR		
REV. APP'D DATE SCALE 1:1 DIMENSIONS IN INCHES [mm]	DRAWN JM 1/6/2006	PART NO. (SEE TABLE) REV. A		SALES DWG NO. FA10656SL REV. A1					
A1 MH 05/12/2006 MPDP0001-ST	ENG APPR. MH 05/12/2006								