


GLASS FILLED
NYLON PLUGS
INCLUDED



PART NO.	CONDUCTOR MATERIAL	T/C TYPE
FA11690	CHROMEL / ALUMEL	K
FA11690-02	IRON / CONSTANTAN	J
FA11690-03	TUNGSTEN / RHENIUM*	C
FA11690-04	CHROMEL / CONSTANTAN	E


*TYPE C USES COMPENSATION WIRE
MAXIMUM JUNCTION TEMPERATURE 250°C

RATINGS	
CONDUCTOR MATERIAL:	SEE TABLE AT LEFT
T/C TYPE:	SEE TABLE AT LEFT
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C
TEMPERATURE WITH PLUG:	-29°C TO 218°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE: TWO PAIR T/C SPADE TYPE
FEEDTHROUGH



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	1/13/2006
B1	MH	05/26/2006	MPC10031-0ST		ENG APPR.	MH	05/26/2006

PART NO. (SEE TABLE) REV. B

SALES DWG NO. FA11690SL REV. B1