


PART NO.	CONDUCTOR MATERIAL	CURRENT
FA12691	COPPER	55 AMPS
FA12691-02	MOLYBDENUM	28 AMPS
FA12691-03	NICKEL	16.5 AMPS
FA12691-04	304 STN STL	3.6 AMPS

RATINGS	
VOLTAGE:	5KV DC
CURRENT:	SEE TABLE AT LEFT
TEMPERATURE:	-25°C TO 205°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

EIGHT 5KV FEEDTHROUGHS



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 7:8	DIMENSIONS IN INCHES [mm]	DRAWN	JM	12/28/2005
A1	MH	04/28/2006	MPST0020-1ST		ENG APPR.	MH	04/28/2006

PART NO. (SEE TABLE) REV. A

SALES DWG NO. FA12691SL REV. A1