



PART NO.	CONDUCTOR MATERIAL	CURRENT WITH PLUG	CURRENT WITHOUT PLUG
FA14313	COPPER	26 AMPS	55 AMPS
FA14313-02	MOLYBDENUM	26 AMPS	28 AMPS
FA14313-03	NICKEL	16.5 AMPS	16.5 AMPS
FA14313-04	304 STN STL	3.6 AMPS	3.6 AMPS

RATINGS		
	WITH PLUG	WITHOUT PLUG
VOLTAGE:	10KV DC	5KV DC
CURRENT:	SEE TABLE AT LEFT	SEE TABLE AT LEFT
TEMPERATURE:	-25°C TO 125°C	-269° TO 450°C

MATES WITH POWERPLUG FP10884-02

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 			TITLE: EIGHT 10KV FEEDTHROUGHS		
REV. APP'D DATE SCALE 1:1.33333 DIMENSIONS IN INCHES [mm]	DRAWN JM 3/1/2006	PART NO. (SEE TABLE) REV. A		SALES DWG NO. FA14313SL REV. A1					
A1 MH 08/28/2006 MPST0043-0ST	ENG APPR. MH 08/28/2006								