

GLASS FILLED
NYLON PLUGS
INCLUDED

| PART NO. | CONDUCTOR MATERIAL | T/C TYPE |
|------------|----------------------|----------|
| FA11719 | CHROMEL / ALUMEL | K |
| FA11719-02 | IRON / CONSTANTAN | J |
| FA11719-03 | TUNGSTEN / RHENIUM* | C |
| FA11719-04 | CHROMEL / CONSTANTAN | E |


*TYPE C USES COMPENSATING WIRE
MAXIMUM JUNCTION TEMPERATURE 250°C

| RATINGS | |
|------------------------------|-------------------|
| CONDUCTOR MATERIAL: | SEE TABLE AT LEFT |
| T/C TYPE: | SEE TABLE AT LEFT |
| TEMPERATURE WITHOUT PLUG: | -269°C TO 450°C |
| TEMPERATURE WITH PLUG: | -29°C TO 218°C |

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE
SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY
REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN
PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE: FIVE PAIR T/C SPADE TYPE
FEEDTHROUGH



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA11719SL REV. B1

| REV. | APP'D | DATE | SCALE 1:1 | DIMENSIONS IN INCHES [mm] | DRAWN | JM | 1/13/2006 |
|------|-------|------------|-------------|------------------------------|-----------|----|------------|
| B1 | MH | 05/26/2006 | MPDP0010-ST | | ENG APPR. | MH | 05/26/2006 |

PART NO. (SEE TABLE) REV. B