



PART NO.	CONDUCTOR MATERIAL	CURRENT
FA13990	COPPER	55 AMPS
FA13990-02	MOLYBDENUM	28 AMPS
FA13990-03	NICKEL	16.5 AMPS
FA13990-04	304 STN STL	3.6 AMPS

RATINGS	
VOLTAGE:	12KV DC
CURRENT:	SEE TABLE AT LEFT
TEMPERATURE:	-269° TO 450°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

EIGHT 12KV FEEDTHROUGHS

PART NO. (SEE TABLE) REV. A



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA13990SL REV. A1

REV.	APP'D	DATE	SCALE 7:8	DIMENSIONS IN INCHES [mm]	DRAWN	JM	4/19/2006
A1	MH	08/15/2006	MPST0035-0ST		ENG APPR.	MH	08/15/2006