



PART NO.	CONDUCTOR MATERIAL	T/C TYPE
FA11689	CHROMEL / ALUMEL	K
FA11689-02	IRON / CONSTANTAN	J
FA11689-03	TUNGSTEN / RHENIUM*	C
FA11689-04	CHROMEL / CONSTANTAN	E

\*TYPE C USES COMPENSATION WIRE  
 MAXIMUM JUNCTION TEMPERATURE 250°C

RATINGS	
CONDUCTOR MATERIAL:	SEE TABLE AT LEFT
T/C TYPE:	SEE TABLE AT LEFT
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C
TEMPERATURE WITH PLUG:	-29°C TO 218°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE: ONE PAIR T/C SPADE TYPE FEEDTHROUGH



REV.	APP'D	DATE	SCALE 1.25:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	1/12/2006
A1	MH	05/26/2006	MPLC0032-ST		ENG APPR.	MH	05/26/2006

PART NO. (SEE TABLE) REV. A

SALES DWG NO. FA11689SL REV. A1