


| PART NO.   | CONDUCTOR MATERIAL | CURRENT   |
|------------|--------------------|-----------|
| FA11672    | COPPER             | 55 AMPS   |
| FA11672-02 | MOLYBDENUM         | 28 AMPS   |
| FA11672-03 | NICKEL             | 16.5 AMPS |
| FA11672-04 | 304 STN STL        | 3.6 AMPS  |

| RATINGS      |                   |
|--------------|-------------------|
| VOLTAGE:     | 5KV DC            |
| CURRENT:     | SEE TABLE AT LEFT |
| TEMPERATURE: | -269°C TO 450°C   |

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

FOUR 5KV FEEDTHROUGHS

PART NO. FA11672 REV. A



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA11672SL REV. A1

| REV. | APP'D | DATE       | SCALE 4:5   | DIMENSIONS IN INCHES [mm] | DRAWN     | JM | 1/12/2006  |
|------|-------|------------|-------------|---------------------------|-----------|----|------------|
| A1   | MH    | 04/28/2006 | MPST0011-11 |                           | ENG APPR. | MH | 04/28/2006 |