



PART NO.	CONDUCTOR MATERIAL	CURRENT WITH PLUG	CURRENT WITHOUT PLUG
FA12633	COPPER	26 AMPS	55 AMPS
FA12633-02	MOLYBDENUM	26 AMPS	28 AMPS
FA12633-03	NICKEL	16.5 AMPS	16.5 AMPS
FA12633-04	304 STN STL	3.6 AMPS	3.6 AMPS

RATINGS		
	WITH PLUG	WITHOUT PLUG
VOLTAGE:	20KV DC	12KV DC
CURRENT:	SEE TABLE AT LEFT	SEE TABLE AT LEFT
TEMPERATURE:	-55°C TO 125°C	-269° TO 450°C

MATES WITH POWERPLUG FP10883-02

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 			TITLE: EIGHT 20KV FEEDTHROUGHS		
REV.	APP'D	DATE	SCALE 1:1.33333	DIMENSIONS IN INCHES [mm]	DRAWN	JM	4/19/2006	PART NO. (SEE TABLE) REV. A	
A1	MH	08/14/2006	MPST0013-ST		ENG APPR.	MH	08/14/2006		SALES DWG NO. FA12633SL REV. A1