

GLASS FILLED  
NYLON PLUGS  
INCLUDED

PART NO.	CONDUCTOR MATERIAL	T/C TYPE
FA13193	CHROMEL / ALUMEL	K
FA13193-02	IRON / CONSTANTAN	J
FA13193-03	TUNGSTEN/ RHENIUM*	C
FA13193-04	CHROMEL / CONSTANTAN	E


\*TYPE C USES COMPENSATING WIRE  
MAXIMUM JUNCTION TEMPERATURE 250°C

RATINGS	
CONDUCTOR MATERIAL:	SEE TABLE AT LEFT
T/C TYPE:	SEE TABLE AT LEFT
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C
TEMPERATURE WITH PLUG:	-29°C TO 218°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE  
SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY  
REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN  
PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE: THREE PAIR T/C SPADE TYPE  
FEEDTHROUGH



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	1/13/2006
A1	MH	05/26/2006	MPDP0022-ST		ENG APPR.	MH	05/26/2006

PART NO. (SEE TABLE) REV. A

SALES DWG NO. FA13193SL REV. A1