



PART NO.	CONDUCTOR MATERIAL	CURRENT WITH PLUG	CURRENT WITHOUT PLUG
FA11674	COPPER	26 AMPS	55 AMPS
FA11674-02	MOLYBDENUM	26 AMPS	28 AMPS
FA11674-03	NICKEL	16.5 AMPS	16.5 AMPS
FA11674-04	304 STN STL	3.6 AMPS	3.6 AMPS

RATINGS		
	WITH PLUG	WITHOUT PLUG
VOLTAGE:	10KV DC	5KV DC
CURRENT:	SEE TABLE AT LEFT	SEE TABLE AT LEFT
TEMPERATURE:	-55°C TO 125°C	-269° TO 450°C

MATES WITH POWERPLUG FP10884-02

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.					THIRD ANGLE PROJECTION 			TITLE: <b>FOUR 10KV FEEDTHROUGHS</b>		
REV.	APP'D	DATE	SCALE 4:5	DIMENSIONS IN INCHES [mm]	DRAWN	JM	1/12/2006	PART NO. (SEE TABLE) REV. A	SALES DWG NO. FA11674SL REV. A1	
A1	MH	04/28/2006	MPST0014-1ST		ENG APPR.	MH	04/28/2006			