

PART NO.	CONDUCTOR MATERIAL	CURRENT WITH PLUG	CURRENT WITHOUT PLUG
FA13460	COPPER	26 AMPS	55 AMPS
FA13460-02	MOLYBDENUM	26 AMPS	28 AMPS
FA13460-03	NICKEL	16.5 AMPS	16.5 AMPS
FA13460-04	304 STN STL	3.6 AMPS	3.6 AMPS


	RATINGS	
	WITH PLUG	WITHOUT PLUG
VOLTAGE:	10KV DC	5 KV DC
CURRENT:	SEE TABLE AT LEFT	SEE TABLE AT LEFT
TEMPERATURE:	-25°C TO 125°C	-25°C TO 205°C

MATES WITH POWERPLUG FP10884-02

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

FOUR 10KV FEEDTHROUGHS



REV.	APP'D	DATE	SCALE 7:8	DIMENSIONS IN INCHES [mm]	DRAWN	JM	2/22/2006
A1	MH	08/25/2006	MPST0014-ST		ENG APPR.	MH	08/25/2006

PART NO. (SEE TABLE) REV. A

SALES DWG NO. FA13460SL REV. A1