



PART NO.	CONDUCTOR MATERIAL	CURRENT
FA11823	COPPER	55 AMPS
FA11823-02	MOLYBDENUM	28 AMPS
FA11823-03	NICKEL	16.5 AMPS
FA11823-04	304 STN STL	3.6 AMPS

RATINGS	
VOLTAGE:	14KV DC
CURRENT:	SEE TABLE AT LEFT
TEMPERATURE:	-25° TO 205°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 			TITLE: FOUR 14KV FEEDTHROUGHS		
REV.	APP'D	DATE	SCALE 1:1.33333	DIMENSIONS IN INCHES [mm]	DRAWN	JM	4/12/2006	PART NO. (SEE TABLE) REV. A	
A1	MH	08/11/2006	FTST0018-ST		ENG APPR.	MH	08/11/2006		SALES DWG NO. FA11823SL REV. A1