



PART NO.	CONDUCTOR MATERIAL	CURRENT WITH PLUG	CURRENT WITHOUT PLUG
FA14055	COPPER	26 AMPS	55 AMPS
FA14055-02	MOLYBDENUM	26 AMPS	28 AMPS
FA14055-03	NICKEL	16.5 AMPS	16.5 AMPS
FA14055-04	304 STN STL	3.6 AMPS	3.6 AMPS

RATINGS		
	WITH PLUG	WITHOUT PLUG
VOLTAGE:	20KV DC	14KV DC
CURRENT:	SEE TABLE AT LEFT	SEE TABLE AT LEFT
TEMPERATURE:	-55°C TO 125°C	-269° TO 450°C

MATES WITH POWERPLUG FP10883-02

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.					THIRD ANGLE PROJECTION 			TITLE: <b>TWO 20KV FEEDTHROUGHS</b>		
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	12/28/2005	<b>PART NO. (SEE TABLE) REV. A</b>	SALES DWG NO. FA14055SL REV. A1	
A1	MH	04/28/2006	MPST0030-0ST		ENG APPR.	MH	04/28/2006			