



PART NO.	CONDUCTOR MATERIAL	CURRENT WITH PLUG	CURRENT WITHOUT PLUG
FA13219	COPPER	26 AMPS	55 AMPS
FA13219-02	MOLYBDENUM	26 AMPS	28 AMPS
FA13219-03	NICKEL	16.5 AMPS	16.5 AMPS
FA13219-04	304 STN STL	3.6 AMPS	3.6 AMPS

RATINGS		
	WITH PLUG	WITHOUT PLUG
VOLTAGE:	20KV DC	14KV DC
CURRENT:	SEE TABLE AT LEFT	SEE TABLE AT LEFT
TEMPERATURE:	-25°C TO 125°C	-25° TO 205°C

MATES WITH POWERPLUG FP10883-02

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 			TITLE: <b>FOUR 20KV FEEDTHROUGHS</b>		 SALES DWG NO. FA13219SL REV. A1
REV.	APP'D	DATE	SCALE 1:1.33333	DIMENSIONS IN INCHES [mm]	DRAWN	JM	4/12/2006	<b>PART NO. (SEE TABLE) REV. A</b>	
A1	MH	08/14/2006	FTST0033-1ST		ENG APPR.	MH	08/14/2006		