


PART NO.	CONDUCTOR MATERIAL	CURRENT
FA12445	COPPER	100 AMPS
FA12445-02	MOLYBDENUM	50 AMPS
FA12445-03	NICKEL	30 AMPS
FA12445-04	304 STN STL	6.5 AMPS

RATINGS	
VOLTAGE:	5KV DC
CURRENT:	SEE TABLE AT LEFT
TEMPERATURE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

FOUR 5KV FEEDTHROUGHS



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 1:1.33333	DIMENSIONS IN INCHES [mm]	DRAWN	JM	4/19/2006
A1	MH	08/14/2006	MPST0018-1ST		ENG APPR.	MH	08/14/2006

PART NO. (SEE TABLE) REV. A

SALES DWG NO. FA12445SL REV. A1