


PART NO.	CONDUCTOR MATERIAL	CURRENT
FA13205	COPPER	330 AMPS
FA13205-03	NICKEL	98 AMPS
FA13205-04	304 STN STL	21 AMPS

RATINGS	
VOLTAGE:	8KV DC
CURRENT:	SEE TABLE AT LEFT
TEMPERATURE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

2 CONDUCTOR FEEDTHROUGH



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 3:4	DIMENSIONS IN INCHES [mm]	DRAWN	MH	02/28/2006
A1	MH	02/28/2006	MPCL0064-0ST		ENG APPR.	MH	02/28/2006

PART NO. (SEE TABLE) REV. A

SALES DWG NO. FA13205SL REV. A1