


PART NO.	CONDUCTOR MATERIAL	CURRENT
FA14944	COPPER	330 AMPS
FA14944-03	NICKEL	98 AMPS
FA14944-04	304 STN STL	21 AMPS

RATINGS	
VOLTAGE:	8KV DC
CURRENT:	SEE TABLE AT LEFT
TEMPERATURE:	-25°C TO 205°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

TWO 8KV FEEDTHROUGHS



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 1:1.33333	DIMENSIONS IN INCHES [mm]	DRAWN	EB	5/22/2006
A1	MH	08/24/2006	FTCL0055-1ST		ENG APPR.	MH	08/24/2006

PART NO. (SEE TABLE) REV. A

SALES DWG NO. FA14944SL REV. A1