

PART NO.	CONDUCTOR MATERIAL	CURRENT
FA10309	304 STN STL	3.6 AMPS
FA10309-02	COPPER	55 AMPS
FA10309-03	NICKEL	16.5 AMPS


RATINGS	
VOLTAGE:	30KV DC
CURRENT:	SEE TABLE AT LEFT
TEMPERATURE:	-80°C TO 450°C*

* CALL SST TO CONFIRMLOWER TEMPERATURE USE

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

30KV FLUTED FEEDTHROUGH

PART NO. (SEE TABLE) REV. B



SALES DWG NO. FA10309SL REV. B1

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	1/6/2006
B1	OG	07/25/2006	FTFL0001-0ST		ENG APPR.	MH	03/21/2006