

| PART NO.   | CONDUCTOR MATERIAL | CURRENT  |
|------------|--------------------|----------|
| FA10917    | COPPER             | 330 AMPS |
| FA10917-03 | NICKEL             | 98 AMPS  |
| FA10917-04 | 304 STN STL        | 21 AMPS  |


| RATINGS      |                   |
|--------------|-------------------|
| VOLTAGE:     | 8KV DC            |
| CURRENT:     | SEE TABLE AT LEFT |
| TEMPERATURE: | -80°C TO 450°C*   |

\* CALL SST TO CONFIRM LOWER TEMPERATURE USE

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

8KV FEEDTHROUGH



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA10917SL REV. A1

| REV. | APP'D | DATE       | SCALE 1:1    | DIMENSIONS IN INCHES [mm] | DRAWN     | JM | 1/6/2006   |
|------|-------|------------|--------------|---------------------------|-----------|----|------------|
| A1   | MH    | 03/21/2006 | FTCL0013-0ST |                           | ENG APPR. | MH | 03/21/2006 |

PART NO. (SEE TABLE) REV. A