



PART NO.	CONDUCTOR MATERIAL	CURRENT
FA12036	COPPER	800 AMPS
FA12036-03	NICKEL	240 AMPS
FA12036-04	304 STN STL	52 AMPS

RATINGS	
VOLTAGE:	8KV DC
CURRENT:	SEE TABLE AT LEFT
TEMPERATURE:	-80°C TO 450°C*

\* CALL SST TO CONFIRM LOWER TEMPERATURE USE

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

8KV FEEDTHROUGH



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA12036SL REV. A1

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	1/12/2006
A1	MH	04/28/2006	FTCL0029-0ST		ENG APPR.	MH	04/28/2006

PART NO. (SEE TABLE) REV. A