


PART NO.	CONDUCTOR MATERIAL	CURRENT
FA13865	COPPER	100 AMPS
FA13865-02	MOLYBDENUM	50 AMPS
FA13865-03	NICKEL	30 AMPS
FA13865-04	304 STN STL	6.5 AMPS

RATINGS	
VOLTAGE:	5KV DC
CURRENT:	SEE TABLE AT LEFT
TEMPERATURE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

5KV FEEDTHROUGH



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	2/22/2006
A1	MH	08/25/2006	FTST0051-02		ENG APPR.	MH	08/25/2006

PART NO. FA13865 REV. A

SALES DWG NO. FA13865SL REV. A1