


PART NO.	CONDUCTOR MATERIAL	CURRENT
FA13900	304 STN STL	3.6 AMPS
FA13900-02	COPPER	55 AMPS
FA13900-03	NICKEL	16.5 AMPS

RATINGS	
VOLTAGE:	30KV DC
CURRENT:	SEE TABLE AT LEFT
TEMPERATURE:	-25°C TO 205°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

30KV FLUTED FEEDTHROUGH

PART NO. (SEE TABLE) REV. A



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA13900SL REV. A1

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	4/19/2006
A1	OG	07/26/2006	FTFL0022-0ST		ENG APPR.	OG	07/26/2006