

| PART No. | TUBE MATERIAL |
|------------|---------------|
| FA14222 | COPPER |
| FA14222-02 | 304 STN STL |


| RATINGS | |
|--------------|-----------------|
| VOLTAGE: | 8KV DC |
| TEMPERATURE: | -80°C TO 450°C* |

* CALL SST TO CONFIRM LOWER TEMPERATURE USE

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

8KV FEEDTHROUGH



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA14222SL REV. A1

| REV. | APP'D | DATE | SCALE 1:1 | DIMENSIONS IN INCHES [mm] | DRAWN | JM | 3/1/2006 |
|------|-------|------------|--------------|---------------------------|-----------|----|------------|
| A1 | MH | 08/25/2006 | FTCL0029-1ST | | ENG APPR. | MH | 08/25/2006 |

PART NO. (SEE TABLE) REV. A