



PART NO.	CONDUCTOR MATERIAL	CURRENT WITH PLUG	CURRENT WITHOUT PLUG
FA14397	COPPER	26 AMPS	55 AMPS
FA14397-02	MOLYBDENUM	26 AMPS	28 AMPS
FA14397-03	NICKEL	16.5 AMPS	16.5 AMPS
FA14397-04	304 STN STL	3.6 AMPS	3.6 AMPS

RATINGS		
	WITH PLUG	WITHOUT PLUG
VOLTAGE:	10KV DC	5KV DC
CURRENT:	SEE TABLE AT LEFT	SEE TABLE AT LEFT
TEMPERATURE:	-25°C TO 125°C	-25° TO 205°C

MATES WITH POWERPLUG FP10884-02

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 			TITLE: 10KV FEEDTHROUGH		
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	3/14/2006	PART NO. (SEE TABLE) REV. A	
A1	MH	06/06/2006	FTST0055-ST		ENG APPR.	MH	06/06/2006		SALES DWG NO. FA14397SL REV. A1